



**FLAT SCREEN**

**Customized**



Wedge wire screens from YUBO are manufactured and distributed as high quality wedge wire screen panels or tubes, and are custom-manufactured to suit specific screens, machines and applications. Making use of a wide range of apertures and profiles on the various wedge wire screen sizes, these screens are specifically designed to reduce pegging in difficult applications.

**Standard tolerances:**

Length and width  $\leq 500$  mm +/- 2 mm

Length and width  $> 500$  mm  $\leq 1500$  mm +/- 3 mm

Length and width  $> 1500$  mm +/- 4 mm

**Maximum dimensions**

Max. surface profile length Max. support profile length

Pitch 17mm / Profile Q25 1300 mm 2000 mm

Pitch 17-25mm / Profile Q35 2700 mm 3000 mm

Pitch 22mm 710 mm 1650 mm

Pitch  $\geq 70$ mm 3000 mm (3) 3400 mm

**Application:** Wastewater treatment solution; Vibrating screens; Wastewater treatment; Bore wells; Food; Beverage; Petroleum; Chemical; Mining; Petrochemical industries.

**Benefits** 

- Very low pressure loss
- Extended product life and increased durability
- Stronger and more durable
- Wide range of profile wires available to suit most applications
- Suited for applications that require support for heavy media
- High-precision slot sizes are available to meet your requirements
- For surface filtration, the V-shaped surface wires allow for easy cleaning by mechanical scraping or backflushing